

Influencer





# Specifications

<b>BROADLOOM</b>	Brand.....	<b>Aladdin Commercial</b>
	Style Name / Number .....	<b>Influencer 30 / AQ207</b>
	Construction .....	Tufted
	Surface Appearance.....	Cut Pile
	Tufted Weight .....	30 oz/yd <sup>2</sup> (1,107 g/m <sup>2</sup> )
	Gauge .....	1/10 (39.37 rows per 10 cm)
	Density .....	<b>6,697</b>
	Dye Method.....	Piece Dyed
	Fiber Type.....	ColorStrand® Nylon
	Stain Release Technology....	Mohawk Protection Plus Stain
	Soil Release Technology .....	Mohawk Protection Plus Soil
	Primary Backing .....	Woven Primary
	Secondary Backing.....	Weldlok®
	Indoor Air Quality .....	Green Label Plus Certified #6678
	NSF 140.....	Gold
	Width.....	12' width (3.66 m)
	Flammability.....	ASTM E 648 Class 1 (Glue Down)
Smoke Density.....	ASTM E 662 Less than 450	
Static Propensity .....	AATCC-134 Under 3.5 KV	
Warranties.....	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty	

<b>BROADLOOM</b>	Brand.....	<b>Aladdin Commercial</b>
	Style Name / Number .....	<b>Influencer 36 / AQ208</b>
	Construction .....	Tufted
	Surface Appearance.....	Cut Pile
	Tufted Weight .....	36 oz/yd <sup>2</sup> (1,221 g/m <sup>2</sup> )
	Gauge .....	1/10 (39.37 rows per 10 cm)
	Density .....	<b>6,697</b>
	Dye Method.....	Piece Dyed
	Fiber Type.....	ColorStrand® Nylon
	Stain Release Technology....	Mohawk Protection Plus Stain
	Soil Release Technology .....	Mohawk Protection Plus Soil
	Primary Backing .....	Woven Primary
	Secondary Backing.....	Weldlok®
	Indoor Air Quality .....	Green Label Plus Certified #6678
	NSF 140.....	Gold
	Width.....	12' width (3.66 m)
	Flammability.....	ASTM E 648 Class 1 (Glue Down)
Smoke Density.....	ASTM E 662 Less than 450	
Static Propensity .....	AATCC-134 Under 3.5 KV	
Warranties.....	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty	

<b>BROADLOOM</b>	Brand.....	<b>Aladdin Commercial</b>
	Style Name / Number .....	<b>Influencer 42 / AQ209</b>
	Construction .....	Tufted
	Surface Appearance.....	Cut Pile
	Tufted Weight .....	42 oz/yd <sup>2</sup> (1,424 g/m <sup>2</sup> )
	Gauge .....	1/10 (39.37 rows per 10 cm)
	Density .....	<b>6,697</b>
	Dye Method.....	Piece Dyed
	Fiber Type.....	ColorStrand® Nylon
	Stain Release Technology....	Mohawk Protection Plus Stain
	Soil Release Technology .....	Mohawk Protection Plus Soil
	Primary Backing .....	Woven Primary
	Secondary Backing.....	Weldlok®
	Indoor Air Quality .....	Green Label Plus Certified #6678
	NSF 140.....	Gold
	Width.....	12' width (3.66 m)
	Flammability.....	ASTM E 648 Class 1 (Glue Down)
Smoke Density.....	ASTM E 662 Less than 450	
Static Propensity .....	AATCC-134 Under 3.5 KV	
Warranties.....	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty	

<b>BROADLOOM</b>	Brand.....	<b>Aladdin Commercial</b>
	Style Name / Number .....	<b>Classic Update / AQ204</b>
	Construction .....	Tufted
	Surface Appearance.....	Cut & Loop
	Tufted Weight .....	28 oz/yd <sup>2</sup> (949 g/m <sup>2</sup> )
	Gauge .....	1/8 (31.50 rows per 10 cm)
	Density .....	<b>6,697</b>
	Dye Method.....	Piece Dyed
	Fiber Type.....	ColorStrand® Nylon
	Stain Release Technology....	Mohawk Protection Plus Stain
	Soil Release Technology .....	Mohawk Protection Plus Soil
	Primary Backing .....	Woven Primary
	Secondary Backing.....	Weldlok®
	Indoor Air Quality .....	Green Label Plus Certified #6678
	NSF 140.....	Gold
	Pattern Repeat .....	0.5" (W) x 0.875" (L)
	Width.....	12' width (3.66 m)
Flammability.....	ASTM E 648 Class 1 (Glue Down)	
Smoke Density.....	ASTM E 662 Less than 450	
Static Propensity .....	AATCC-134 Under 3.5 KV	
Warranties.....	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty	

**Aladdin**<sup>™</sup>  
COMMERCIAL

Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

Mohawk is providing this architect folder for the purpose of promoting our commercial business. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations. We recommend the use of chair pads on all commercial installations.

For current and complete specifications please call tech support at 888-387-9881 or visit [www.AladdinCommercial.com](http://www.AladdinCommercial.com) | 800.233.4490



Up to 2,000 sq. yds. available within 10 business days or less



